Vacuum Filtration System

Features

► For large number of samples

MultiVac 310 / 610 - MS - A are economical models for large sample filtration. Each system includes Alligator 200 diaphragm liquid pump, manifold and magnetic filter holders.

► Time-saving and space-saving

The vacuum source has built in a liquid pump which can be connected directly to manifold without waste bottle. Save 40% bench space and simplify filtration process.

Light and handy aluminum

The manifold is made of aluminum which is autoclavable, light and cost-effective.

Magnetic filter holder is included

Magnetic filter holder allows one-handed operation and prevents the membrane from being twisted or torn.

International certification

CE certification IP 64 protection (Alligator 200) RoHS certification (Alligator 200)

One-Year Warranty (Alligator 200)

Applications

- Suspended solid test
- Microbiological test
- Vacuum filtration

Ordering Information

180311-01(02)-A 180611-01(02)-A

MultiVac 310 / 610 - MS - A, Vacuum Filtration System, complete set includes:

- *Alligator 200, Diaphragm Liquid Pump
- *MultiVac 310 / 610 MS, 3/6 Places Aluminum Manifold

*MF 3, 300 ml Magnetic Filter Holder with lid kit (3/6 pcs)

*Silicone Tube (2 pcs)





Specification

Model	MultiVac 310 - MS - A	MultiVac 610 - MS - A
Power	DC24V, 1.8A	
Max. vacuum	313 mbar	
Max. liquid flow rate	4.5 L/min	
Motor	60W Brushless DC Motor	
Noise level	60 dB	
Hose barb	ID8	
Material contact with filtrate	SS316, FKM, Silicone, PP, PPS	
Model	MultiVac 310 - MS	MultiVac 610 - MS
Number of branch	3	6
Filter holder	MF 3, 300 ml x 3	MF 3, 300 ml x 6
Filter diameter	47 mm	47 mm
Material contact with filtrate	Aluminum	Aluminum



Vacuum Filtration System

Features

► For microbiological filtration

MultiVac 301 / 601 - MB - A , include Alligator 200 diaphragm liquid pump, manifold, burner, stainless steel funnels and MCE membrane, are designed for a large number of samples in microbiological test. All wetted parts of manifold are made of SS316 stainless steel, which can be fast sterilized by flame.

► Time-saving and space-saving

The vacuum source has built in a liquid pump which can be connected directly to manifold without waste bottle. Save 40% bench space and simplify filtration process.

Quick-assembly and disassembly

Each component of manifold can be easily removed for cleaning and autoclaving.

Innovative vent valve design

An adjustable vent valve integrated with the pipe can eliminate water hammer phenomenon and help drain out residual waste water.

► International certification

CE certification IP 64 protection (Alligator 200) RoHS certification (Alligator 200)

► One-Year Warranty (Alligator 200)

Applications

- Suspended solid test
- ► Microbiological test
- ► Vacuum filtration

Ordering Information

180301-01(02)-A 180601-01(02)-A

MultiVac 301 / 601 - MB - A, Vacuum
Filtration System, complete set includes:
*Alligator 200, Diaphragm Liquid Pump
*MultiVac 300 / 600 - MB, 3/6 Places
Stainless Steel Manifold
*SF, 100 ml Stainless Steel Funnel (3/6 pcs)
*Dragon 100, Torch Burner
*MCE Membrane, 47 mm, 0.45 µm, 200/PK
*Silicone Tube (2 pcs)





Specification

Model	MultiVac 301 - MB - A	MultiVac 601 - MB - A
Power	DC24V, 1.8A	
Max. vacuum	313 mbar	
Max. liquid flow rate	4.5 L/min	
Motor	60W Brushless DC Motor	
Noise level	60 dB	
Hose barb	ID8	
Material contact with filtrate	SS316, FKM, Silicone, PP, PPS	
Model	MultiVac 301 - MB	MultiVac 601 - MB
Number of branch	3	6
Funnel	SF stainless steel funnel, 100 ml x 3	SF stainless steel funnel, 100 ml x 6
Filter diameter	47 mm	47 mm
Material contact with filtrate	SS316	SS316